

DECLARATION OF PERFORMANCE

Nº DoP – 1030

Unique identification code of the product-type:

1030 (TOPCOLA FLEX SUPER)

Intended use/es:

Tile adhesive (C2TE) for applying tiles on walls and floors, for indoor and outdoor.

Manufacturer:

TOPECA, Lda,
Rua D. Nuno Álvares Pereira, 53, 2490-114 Cercal – Ourém, PORTUGAL
Tel.: 00 351 – 249 580 070 / Fax.: 00 351 – 249 580 079
www.topeca.com

Notified body/ies:

ITECONS - Instituto de Investigação e Desenvolvimento Tecnológico para a Construção, Energia, Ambiente e Sustentabilidade nº 2211.

Declared performance

Harmonised standard: EN 12004:2007+A1:2012		System (s) of AVCP
Essential Characteristics	Performance	
Reaction to fire	Class E	4 and 3
Release of dangerous substances	See MSDS	
Bond strength, as:		
Initial tensile adhesion strength	≥ 1 N/mm ²	
Durability for:		
Tensile adhesion strength after heat ageing	≥ 1 N/mm ²	
Tensile adhesion strength after water immersion	≥ 1 N/mm ²	
Tensile adhesion strength after freeze-thaw cycles	≥ 1 N/mm ²	

MSDS – Material Safety Data Sheet - AVCP – Assessment and verification of constancy of performance;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) N^o 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ourém, August 6, 2015



Francisco Nunes
(Technical Manager)