

# DECLARATION OF PERFORMANCE

Nº DoP – 101803-01

1. **Unique identification code of the product-type:** TOPELASTIC K2.
2. **Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to nº 4 Article 11º:**  
Component A: (time, date, number) marked on the packaging.  
Component B: (number, date, time) marked on the packaging.
3. **Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**  
Tile adhesive (C1TE) for applying tiles on walls and floors, for indoor and outdoor.
4. **Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to nº5 Article 11º:**  
TOPECA, Lda,  
Rua D. Nuno Alvares Pereira, 53, 2490-114 Cercal – Ourém, PORTUGAL  
Tel.: 00 351 – 249 580 070 / Fax.: 00 351 – 249 580 079  
[www.topeca.com](http://www.topeca.com)
5. **Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in nº2 article 12º.**  
Not applicable
6. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**  
System 3
7. **In case of the declaration of performance concerning a construction product covered by a harmonised standard:**  
CTCV – Technological Centre for Ceramics and Glass (nº855) and Topeca, performed test of performance under system 3 and issued the respective test report:  
nº process: 3.1.5.24232.
8. **In case of the declaration of performance concerning a construction product for which a European technical assessment has been issued:**  
Not applicable.
9. **Declared performance**

Essential Characteristics	Performance	Test Standard	Harmonised Technical Specification
Reaction to fire	Class E		EN 12004:2007+A1:2012
Release of dangerous substances	See MSDS		
<b>Bond strength, as:</b>			
Initial tensile adhesion strength	≥1 N/mm <sup>2</sup>	EN 1348	
<b>Durability for:</b>			
Tensile adhesion strength after heat ageing	≥1 N/mm <sup>2</sup>	EN 1348	
Tensile adhesion strength after water immersion	≥0.5 N/mm <sup>2</sup>	EN 1348	
Tensile adhesion strength after freeze-thaw cycles	≥0.5 N/mm <sup>2</sup>	EN 1348	

MSDS – Material Safety Data Sheet

Where pursuant to Article 37º or 38º the Specific Technical Documentation has been used, the requirements with which the product complies:  
Not applicable.

10. **The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed for and on behalf of the manufacturer by:

Ourém, June 28<sup>th</sup> 2013



Francisco Nunes  
(Technical Manager)