

topfix



TECHNICAL DATA SHEET

TOPECA, Lda
Rua do Mosqueiro
2490-115 Cercal – Ourém
PORTUGAL

Tel.: 00 351 – 249 580 070
Fax.: 00 351 – 249 580 079

TOPECA
FÁBRICA DE PRODUTOS PARA CONSTRUÇÃO

geral@topeca.pt
www.topeca.pt

topfix

special products

primer, adhesion promoter



reference:

- Topfix with sand
- Topfix without sand

use

Bonding primer that favors the binding of single-layer plasters.

Use in interior or exterior, walls and ceilings.

Use in smooth concrete, old paint (well adherent and solid) and other without absorption surface (contact us).

Ready to apply, easy to apply. Can be applied neat.

Quick drying, allowing the application of the coating on the day.

Water-based product, non-flammable.

Regulates the surface porosity.

surface

- Smooth concrete;
- Ancient Painting;
- Surfaces without absorption;
- Other (contact us).



topfix

primer, adhesion promoter

special products

recommendations

Wash tools with water after use.

Do not apply with rain in the sweltering heat or hot surfaces.

composition and characteristics

Composition:

Resins in water dispersion, specific additives and silica sand - Reference with sand.

Resins in water dispersion, specific additives - Reference without sand.

Characteristics:

PH = 7-8.

Drying time: 1-6 hours.

Application temperature: 5°C to 30°C.

Density: 1180 kg/m³ (with sand);

Density: 1000 kg/m³ (without sand)

NOTE: Results obtained from laboratory tests, under normal conditions (T = 20°C) may vary depending on application conditions.

colour

Yellow - Topfix with sand;

White - Topfix without sand

consumption

Product diluted: 300 g/m²
corresponding to 200g Topfix/m²

available in

Bucket of 20 kg.

storage

1 year from the date of manufacture in unopened package and under the ice and heat.



topfix

primer, adhesion promoter

special products

preparation of surface

The concrete must be firm, dry and clean, without residual cement laitance parting compounds or oils.

Rinse with high pressure water (40 to 80 bar).



application

Mix 2 volumes of Topfix with a volume of water.



Apply Topfix with sand, with roll of wool.

During application stir the product to avoid sediment.

The Topfix without sand can be applied with roll of wool or spray machine



The lining (plaster / single-layer) should be applied on the Topfix dry and sticky (about 30 minutes after application of Topfix, depending on weather).

