

# rebetop primário



## TECHNICAL DATA SHEET

TOPECA, Lda  
Rua do Mosqueiro  
2490-115 Cercal – Ourém  
PORTUGAL

Tel.: 00 351 – 249 580 070  
Fax.: 00 351 – 249 580 079

**TOPECA**  
FÁBRICA DE PRODUTOS PARA CONSTRUÇÃO

[geral@topeca.pt](mailto:geral@topeca.pt)  
[www.topeca.pt](http://www.topeca.pt)

# rebetop

## primário

special products

pigmented liquid paint primer



### use

Is a general purpose pigmented liquid paint primer.

Is a effective method of preparing substrates by reducing suction and providing a colour wash prior to the application of many Topeca finishers, organic coatings (Rebetop Gran and Rebetop Decor), powder coatings (Rebetop Color). The Primary Rebetop is ready to use.

### surface

- Plaster;
- Render;
- Mortar for regularization;
- Mortar bus (tinned).



# rebetop primário

pigmented liquid paint primer

special products

## recommendations

Do not apply: During very humid weather conditions or if rain is forecast, during extreme hot weather or when exposed to strong winds, on damp or frozen / thawing surfaces, on horizontal or sloping surfaces exposed to wet conditions.

## composition and characteristics

### Composition:

Acrylic resins in dispersion, fillers and special additives.

### Characteristics:

pH: 7-8.

Dry: 1-8 hours depending on temperature and substrate.

Apply: +5 ° C to 30 ° C.

NOTE: Results obtained from laboratory tests, under normal conditions (T = 20 ° C) may vary depending on application conditions.

## colour

White. Others: see color catalog Rebetop Color, and Gran Rebetop Rebetop Decor.

## consumption

200g/m<sup>2</sup> depending on the absorption of the wall and how to apply.

## available in

Bucket of 20 kg

## storage

1 year from the date of manufacture in original container under the ice and strong heat.



# rebetop primário

pigmented liquid paint primer

special products

## preparation of surface

Substrates must be clean, sound, dry and free of dust or other contamination.



## application

Mix before applying, with mixer at low speed.



Apply a layer Primary Rebetop with a roll of wool or brush.  
 Leave a regular layer.  
 Allow to dry 2-4 hours before applying the organic coating.

