



TECHNICAL DATA SHEET

TOPECA, Lda
Rua D. Nuno Alvares Pereira, 53
2490-114 Cercal – Ourém
PORTUGAL

Tel.: 00 351 – 249 580 070
Fax.: 00 351 – 249 580 079

TOPECA
FÁBRICA DE PRODUTOS PARA CONSTRUÇÃO

geral@topeca.pt
www.topeca.pt

toplimpa

extra

special products

product line scale cleaning



use

Toplimpa Extra is a cleaner specifically designed for cleaning facades coated with ceramic, unpolished granite, slate, glass blocks, others see us.

Specially designed to remove lime, cement residue and efflorescence limestone.

Product is easy to apply, but requires that they take all protective measures during manipulation.

Promotes deep cleaning and uniform.

surface

- Ceramic Surfaces;
- Concrete;
- Stone (granite and slate);
- Glass blocks;
- Tiles.



toplimpa extra

product line scale cleaning

special products

recommendations

Do not mix with alkaline products.

CAN NOT APPLY ON METALS.

In case of being in contact with metals, rinse immediately with water.

Do not use on marble, limestone or polishing stones, since the product attacks these materials.

Avoid excessive applications so as not to damage the stand if the first application is not satisfactory should be repeated until the desired degree of cleanliness.

During application of Toplimpa Extra wear gloves and eye protection with the most care in handling this product, because it is a corrosive product.

It is advisable to practice tests beforehand.

Apply Toplimpa Extra in well ventilated areas.

Use only plastic utensils including spray.

composition and characteristics

Composition:

Acid solution, specific additives and surfactants;

Characteristics:

Density: 1.120 g/cm³

pH: 1.0;

Time to act: 5-10 minutes, then wash with water.

colour

Dark brown

consumption

100 -400ml/m²

available in

Recipiente de 5 litros.

storage

24 months from the date of manufacture in original unopened container, away from moisture and sunlight.



toplimpa extra

product lime scale cleaning

special products

preparation of surface

Protect all areas that may be damaged during application Toplimpa Extra.
In situations wherein the support is too dry cleaning, previously wet with water.
Apply preferably on damp substrates.



application

The Toplimpa Extra can be used pure or diluted with water (up to 10 % water) depending on the degree of soiling.
Spray the product on the entire surface to be cleaned, allowing it to act for 5-10 minutes.
Clear water jet in order to clean and neutralize the surface.
In case of very persistent stains, repeat the operation.

