



### THE ADVANTAGES OF FLOORPAN LAMINATE FLOORING

	FAST AND EASY ASSEMBLY		SUITABLE FOR UNDERFLOOR HEATING
	RESISTANT TO UV RAYS		RESISTANT TO POINT STRIKES
	ENVIRONMENTALLY FRIENDLY	<b>HDF</b>	BASE PANEL, HIGH DENSITY FIBERBOARD
	RESISTANT TO CIGARETTE FIRE		RESISTANT TO SCRATCH
	EASILY CLEANED AND MAINTAINED, HYGIENIC		NOT AFFECTED BY STAINS
	RESISTANT TO FURNITURE WHEEL ABRASION	<b>E1</b>	E1 GRADE

### LAMINATE FLOORING CLASSIFICATION

CLASS	21	22	23	31	32	33	34
UTILIZATION	AC1	AC2	AC3		AC4	AC5	AC6
ABRASION RESISTANCE	≥ 500	≥ 1000	≥ 2000		≥ 4000	≥ 6000	≥ 8500
RESISTANCE TO STAINS	Min. 4 (group 1 and 2) Min. 3 (group 3)		Min. 5 (group 1 and 2) Min. 4 (group 3)			Min. 5 (group 1, 2 and 3)	

PRODUCT	PANEL SIZE	THICKNESS	SURFACE	PANEL / PACKAGE	PACKAGE / m <sup>2</sup>	PACKAGE / PALLET	PACKAGE kg
FLOORPAN FIX	7x197x1205 mm	7 mm	Authentic	12 Pieces	2,85 m <sup>2</sup>	60 Pieces	~17 kg

SE: SELECT / KASTAMONU

Enjoy Comfort Anywhere With Floorpan!



TECHNICAL DATA SHEET			
FLOORPAN FIX		7 MM - CLASS 31 - AC3	
THICKNESS	mm	7	EN 13329+A1
WIDTH	mm	197	EN 13329+A1
LENGTH	mm	1205	EN 13329+A1
SURFACE		Authentic	
EUROPEAN STANDARD			EN13329
PACKAGE THE DETAILS		12 piece / 1 package	
PIECE		2,849 m <sup>2</sup>	
M <sup>2</sup>		17 kg	
KG			
PALLET THE DETAILS		60 package / 1 pallet	
PIECE		170,94 m <sup>2</sup>	
M <sup>2</sup>		1060 kg	
KG			
CLASS	-	31	EN 13329+A1
ABRASION RESISTANCE	-	AC3	EN 13329+A1
THICKNESS SWELLING	%	≤18	ISO 24336
RESISTANCE TO IMPACT	SMALL BALL	N	≥8
	LARGE BALL	mm	≥500
WARRANTY DOMESTIC / COMMERCIAL	Years	10/5	-
RESISTANCE TO STAINING	-	Min. 5 (group 1 and 2) Min. 4 (group 3)	EN 438
SURFACE SOUNDNESS	N/mm <sup>2</sup>	≥1.0	EN 13329+A1
LOCK STRENGTH	LENGTH	kN/m	-
	WIDTH	kN/m	-
EFFECT OF A CASTOR CHAIR	25,000 Cycles	No Damage	EN 425:2002
EFFECT OF A FURNITURE LEG	-	No Damage	EN 424
OPENING BETWEEN ELEMENTS	mm	≤0,20	EN 13329+A1
HEIGHT DIFFERENCE BETWEEN ELEMENTS	mm	≤0,15	EN 13329+A1
MOISTURE CONTENT	%	4-10	EN 322
FIRE RESISTANCE	Class	C <sub>s</sub> S1	EN 9239-1
FORMALDEHYDE EMISSION	mg/m <sup>3</sup> h	≤3,5 (E1)	EN 12460-3



Our products can also be produced with FSC and CARB certification upon request.